

## SERIES : ADT-8000

### Features & Benefits

- : Stainless Steel wetted parts
- : Excellent resistance to corrosive processes
- : Small figure design, any position to install, Various optional signal outputs.

### Application

- : Hydraulic Pressure, Water Pressure, Medicament and Sanitation, Air Measure etc.
- : Zero & Span Adjustable,

### SPECIFICATION

|                            |                                                       |
|----------------------------|-------------------------------------------------------|
| <b>Range</b>               | : As per table                                        |
| <b>Accuracy</b>            | : $\pm 0.5\%$ FS (0.25% FS optional)                  |
| <b>Output</b>              | : 4 - 20mA ADC 2Wire (0-5V / 0-10V DC 2m V/V, Others) |
| <b>Input Voltage</b>       | : 24Vdc (10-36Vdc)                                    |
| <b>Operating Temp.</b>     | : - 40°C-85°C                                         |
| <b>Over Pressure</b>       | : 150% over Range                                     |
| <b>Electric Connection</b> | : DIN Connector                                       |
| <b>Process Connection</b>  | : 1/4" BSP, 1/2" BSP, Other                           |



| Sr. No. | Item                                       | Range                                                               | Price/Each |
|---------|--------------------------------------------|---------------------------------------------------------------------|------------|
| 1       | Gauge Pressure Transmitter                 | 10, 16, 25, 40, 60, 100, 150, 250, 400, 600 Bar                     |            |
| 2       | Gauge Pressure Transmitter                 | 0-1, 1.6, 2.5, 4, 6, 1000 & 1800 Bar                                |            |
| 3       | Vacuum Pressure Transmitter                | (-) 760mmHG to 0Bar                                                 |            |
| 4       | Compound Pressure Transmitter              | (-) 1 to +1, (-)1 to +3, (-)1 to +5, & (-)1 to +9Bar                |            |
| 5       | Front Flush Diaphragm Pressure Transmitter | 0-1, 2.4, 6, 10, 25, 40 Bar, 1/2" BSP/NPT-M                         |            |
| 6       | Low Range Pressure Transmitter             | 0-1000, 2000, 4000, 5000, 7500mmWC, 1/4BSP NPT-M                    |            |
| 7       | Optional                                   | 0-10V DC Output in Pressure Transmitter excluding SMART Transmitter |            |

**Corporate & Mktg. Office** : 165, G.I.D.C. Makarpura, Vadodara 390 010. **Tel.** : +91 - 265 - 2643550, 2646021.  
**Fax** : + 91 - 265 - 2641054 ■ **E-mail** : marketing@altopindustries.com

**Factory** : 392 , 419-A, GIDC, Makarpura, Vadodara - 390 010.  
**Tel.** : 0265-2658480 ■ **E-mail** : support@altopindustries.com

**MUMBAI** : 5, Turakhia Park, Shopping Complex, Building No. 1, Next to Corporation Bank, M. G. Road, Kandivali (W) MUMBAI - 400 067. ■ **Tel.** : (022) 2806 6032 / 2806 6036 ■ **Fax** : (022) 2862 9113  
**Email** : bombay@altopindustries.com



**ALTOP Industries Ltd.**

PROCESS CONTROL INSTRUMENTATION

CIN - U91110GJ1993PLC018831

<http://www.altopindustries.com>