

ATCAL 3001 - A

'Tubecal' Temperature Calibrator is a tube furnace used for calibration of Temperature Sensors. These are electrically heated from outside, controlled using a precision Auto Tune PID temp. controller to maintain a stable preset temperature. The placement of electrical heaters are designed in such a way that the temperature inside furnace remains stable throughout the inner volume. The stability is further improved using a high temperature alloy block insert with drilled Wells in a concentric



Model	: TUBECAL 900
Temp. Range	: 300 to 900°C
Stability	: $\pm 0.3^{\circ}\text{C}$
Uniformity	: $\pm 2^{\circ}\text{C}$
Resolution	: 1°C
Accuracy	: 0.5 % of F.S.
Heating time	: 90 Minutes.
Power Supply	: 230 V AC $\pm$ 1% 50 Hz
Power Consumption	: 4 KW
Dimensions	: 750 (L) x 575 (W) x 1065 (H)
Weight in Kgs.	: 150 Kg.
Standard Accessories	: Instruction Manual
Optional accessories (with extra price)	: 1) Metal Sleeves 2) Spare Heaters 3) Master Sensors

Corporate & Mktg. Office : 165, G.I.D.C. Makarpura, Vadodara 390 010. Tel. : +91 - 265 - 2643550, 2646021.
Fax : + 91 - 265 - 2641054 ■ **E-mail** : marketing@altopindustries.com

Factory : 392 , 419-A, GIDC, Makarpura, Vadodara - 390 010.
Tel. : 0265-2658480 ■ **E-mail** : support@altopindustries.com

MUMBAI : 5, Turakhia Park, Shopping Complex, Building No. 1, Next to Corporation Bank, M. G. Road, Kandivali (W) MUMBAI - 400 067. ■ **Tel.** : (022) 2806 6032 / 2806 6036 ■ **Fax** : (022) 2862 9113
Email : bombay@altopindustries.com



ALTOP Industries Ltd.
 PROCESS CONTROL INSTRUMENTATION
 CIN - U91110GJ1993PLC018831
<http://www.altopindustries.com>